

WIL - LRXXXX		- XXXX		D		024		- 450		MF		X5.0		O		M12WM12W	
LWXXXX	LED white	2700	2700 Kelvin	A	AC	012	12 V	145	145 mm	MF	Magnet mounting	X0.3	elec. wire 0.3 m	O	orange wire	M12GXXXX	M12 male straight
LBXXXX	LED blue	4000	4000 Kelvin	D	DC	024	24 V	240	240 mm	SX	screw mounting	X1.5	elec. wire 1.5 m	B	black wire	M12GM12G	M12 male straight to M12 female straight
LGXXXX	LED green	5700	5700 Kelvin	...	...	...	...	350	350 mm	MP	magnetic point mounting	X3.0	elec. wire 3.0 m	G	green wire	M12WXXXX	M12 angled male
LRXXXX	LED red	6500	6500 Kelvin	XXXX		XXXX		450	450 mm	CX	clip mounting	X5.0	elec. wire 5.0 m	...	...	M12GM12W	M12 male angled straight to M12 female
LYXXXX	LED yellow	XXXX	different wavelengths					555	555 mm	...	...	10.0	elec. wire 10 m	...	...	M12WM12W	M12 angled male to M12 female angled
LRYGXX	LED (red, yellow, green)	XXXX	place holder	...		...		655	655 mm			...	...			CVPXXXXXX	Cigarette vehicle plug
LRGBXX	LED (red, green, blue)	...	...					765	765 mm			...	...			XXXXXXXXXX	open cable end
LRGBWX	LED (red, green, blue, white)	...	...					860	860 mm			...	...			...	...
...	...	...	...					...	...			...	...			...	...