

APP1



Passende Klemmen


[illegible]

APP2




2.5 / 75.51 / 45.15		
-60 °C		
130 °C		
Wemid		
V-0		
Typ	VPE	Best.-Nr.
APP 2	50	2489090000
A3C 1.5		1552740000
A3C 1.5 PE		1552670000
A4C 1.5		1552690000
A4C 1.5 PE		1552660000
APGTB 1.5 FT 3C/1		2482180000
APGTB 1.5 PE 3C/1		2482230000
ADT 2.5 2C		1989800000
A2C 2.5 /DT/FS		1989900000
A2C 2.5 PE /DT/FS		1989890000
A3C 2.5		1521740000
A3C 2.5 PE		1521670000
A4C 2.5		1521690000
A4C 2.5 PE		1521540000
APGTB 2.5 FT 3C/1		1514000000
APGTB 2.5 PE 3C/1		1513890000
AFS 2.5 CF 2C BK		2466530000
AFS 2.5 CF 2C 12V BK		2466610000
AFS 2.5 CF 2C 24V BK		2466600000
A2C 4		2051180000
A2C 4 PE		2051360000
A3C 4		2051240000
A3C 4 PE		2051410000
A4C 4		2051500000
A4C 4 PE		2051560000
ADT 4 2C		2429850000
AFS 4 2C BK		2429860000
A2C 6		1992110000
A2C 6 PE		1991810000

APP3

[illegible]

Trennwände

APP4



Maße	
Breite / Höhe / Tiefe	mm
Dauergebrauchstemperatur, min.	
Dauergebrauchstemperatur, max.	
Werkstoff	
Brennbarkeitsklasse nach UL 94	
Bestelldaten	
	dunkelbeige
	Passende Klemmen
Hinweis	

2.5 / 89.15 / 54.85		
-60 °C		
130 °C		
Wemid		
V-0		
Typ	VPE	Best.-Nr.
APP 4	50	2489110000
APGTB 1.5 2T 4C/2		2485840000
APGTB 1.5 2T PE 4C/2		2485870000
A2T 1.5		2469370000
A2T 1.5 PE		2469410000
A2T 2.5		1547610000
A2T 2.5 PE		1547680000
APGTB 2.5 2T 4C/2		1548060000
APGTB 2.5 2T PE 4C/2		1548160000

