

CERTIFICATE FI 29995



Our Ref. 289452-1

Product	Connector for power cables
Type	WPD 130, WPD 230, WPD 330, WPD 131, WPD 231 WPD 132, WPD 232 WPD 133, WPD 233
Trade mark	Weidmuller
Certificate Holder	Weidmüller Interface GmbH & Co KG P.O.Box 3030 D-32760 DETMOLD, GERMANY
Manufacturer	Hora - Werk GmbH Lange Str. 65 D-32257 BUNDE, GERMANY
Technical information	See the Appendix to this Certificate
Other information	See the Appendix to this Certificate
The product is certified according to the following standard(s)	EN 60947-7-1:2009 EN 60947-7-2:2009
Validity	This certificate is valid until 26 June 2022 provided that the Conditions for FI certification are met. This certificate includes the right to use the FI mark under the condition that product changes (if any) will be approved at SGS Fimko before the product is brought onto market.
Directive information	The certified product(s) fulfils requirements of above mentioned standard(s) which are harmonised under the Low Voltage Directive (2014/35/EU) at the date of issue of the certificate.
Date of issue	26 June 2017
Signature	SGS Fimko Ltd  Sixten Lökfors Project Manager

This certificate has 2 appendixes



This certificate is issued by the company under its General Conditions for Certification Services accessible at <http://www.sgs.fi/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitations of liability defined therein and in the Test Report here above mentioned which findings are reflected in this certificate. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Fimko Ltd.

Särkiniementie 3 P.O.Box 30 FI-00211 Helsinki, Finland
t. +358 9 696 361 f. +358 9 692 5474 www.sgs.fi

Business ID 0978538-5

Member of the SGS Group (SGS SA)

Appendix 1 to Certificate: 29995

Manufacturing site

Hora - Werk GmbH
Grabenstrasse 22-24
D-32257 BUNDE, GERMANY

Additional information



WPD 130, WPD 230, WPD 330:
WPD 330 consists of 3 pcs WPD 130 connectors
Cu 4 – 50 mm²
In 150 A, Un 1000 V AC / DC, Uimp 8 kV
Tightening torque 10 Nm
Material of the cover: PA6 / grey, blue, yellow green, brown, black

WPD 131, WPD 231:
Cu 10 – 95 mm²
In 232 A, Un 1000 V AC / DC, Uimp 8 kV
Tightening torque 19 Nm
Material of the cover: PA6 / grey, blue, yellow green, brown, black
and grey/grey/grey
grey/blue/yellow-green
yellow-green/grey/blue
red/black/grey

Connector body in phase-, neutral- and earthing connector is same.
Only colour of connector's top part is changing.

WPD 132, WPD 232:
70 - 185 mm²
In 353 A, U 1000 V AC/DC, Uimp 8 kV
Tightening torque 25 Nm
Material of the cover: PA6 / grey, blue, yellow green, brown, black

WPD 133, WPD 233
Cu 120 - 300 mm²
In 520 A, U 1000 V AC/DC, Uimp 8 kV
Tightening torque 45 Nm
Material of the cover: PA6 / grey, blue, yellow green, brown, black